



SILICONE GREASE

LUBRICANT ON A 100% SILICONE BASE



TECHNICAL PROPERTIES

Temperature resistance: -60°C - +200°C

TECHNICAL SPECIFICATIONS

Chemical base: 100% pure silicones

Colour: White (Transparent)

Viscosity: approx. Pasty

Density: approx. 1 g/cm³

STORAGE CONDITIONS

At least 24 months in the unopened package and stored between +5°C and +25°C. Limited shelf life after opening. Close the container properly and store in a dry, cool and frost-free location.

PRODUCT DESCRIPTION

Lubricant for hydrants and valves on a 100% silicone base.

FIELD OF APPLICATION

For or metals and synthetics. Also suitable for lubricating hinges, (sliding) doors, windows, drawers, rails and roller bearings and for maintaining motorcycles, bicycles, scooters, machinery, (garden) tools and sports equipment. Prevents (door) rubbers from freezing

PROPERTIES

- High chemical resistance
- Not soluble in water
- Rust and corrosion resistant
- Water repellent
- Water resistant
- Electrically insulative

QUALITY LABELS/STANDARDS

Certificates: ACS: In accordance with the positive lists of ACS (Attestation de Conformité Sanitaire). Certificate IPL 17 CLP NY 025.

PREPARATION

Preliminary surface treatment: Make sure that the surface is clean, dry, and free of grease.

APPLICATION

Directions for use:

Coat surface thinly and evenly.

Points of attention: Treated surfaces are not paintable.